

This listing of claims will replace all prior versions, and listing, of claims in the application:

Listing of Claims:

1. (Amended) A printed circuit board having a wiring connection structure for interconnecting wiring circuit traces on a plurality of circuit trace layers applied on a plurality of printed circuit board layers and electrically isolated there between by the printed circuit board layers and having a printed circuit board multi-layer structure, characterized by:

a through hole having a non-circular shaped cross section normal to a longitudinal axis of the through ~~hole~~ and having an interior wall that vertically extends through and intersects and exposes at least two wire circuit traces and having a plating of conductive material applied to the interior wall electrically connecting the at least two wire circuit traces.

2. (Currently pending) A printed circuit board having an EMI shielding structure for shielding wiring circuit traces on a plurality of circuit trace layers applied on a plurality of printed circuit board layers and electrically isolated there between by the printed circuit board layers and having a printed circuit board multi- layer structure, characterized by:

a trench having a rim about an opening of the trench at a top printed circuit board layer and said trench extending through a plurality of

printed circuit board layers to a grounding plane exposing said grounding plane and said trench having an interior wall with a conductive plating material applied over said interior wall and said trench having a length greater than two times a breadth of said trench and wherein the trench extends completely around an area of the printed circuit board and wherein said conductive plating material electrically connects to said exposed grounding plane.

3. (Currently pending) A printed circuit board having a wiring connection structure for interconnecting at least two wire traces therein, characterized by:

a first wire trace applied to a main surface of a printed circuit board layer and having a first terminal landing pad with a first through hole there through, said first through-hole having a non-circular shaped cross section normal to the longitudinal axis of the first through hole and having an inner wall;

a first insulation layer formed over said first wire trace having a second through hole of identical cross sectional geometry to and vertically aligned with the first through hole and the second through hole having an inner wall; and

a second wire trace applied to the first insulation layer having a second terminal landing pad with a third through hole having identical

geometry to and vertically aligned with the first through hole and the third through hole having an inner wall; and wherein the inner wall of the first through hole, the inner wall of the second through hole, and the inner wall of the third through hole are plated with an electrically conductive material forming a plated hole with a non-circular shaped cross section that vertically intersects the first and second terminal pads and electrically connects the first wire trace and the second wire trace.

4. (Currently pending) The printed circuit board of claim 3, wherein the non-circular shaped cross section of the plated hole is irregular.

5. (Currently pending) The printed circuit board of claim 3, wherein the non-circular shaped cross section of the plated hole is "U" shaped.

6. (Currently pending) The printed circuit board of claim 3, wherein the non-circular shaped cross section of the plated hole is "L" shaped.

7. (Currently pending) The printed circuit board of claim 3, wherein the non-circular shaped cross section of the plated hole is "+" cross-shaped.

8. (Currently pending) The printed circuit board of claim 3, wherein the first through hole has a shaped continuous curved cross section centered on a circumference diameter of a standard single diameter circular profile micro via and is wholly contained within or extends beyond the perimeter defined by the circumference diameter.

9. (Currently pending) A printed circuit board having a reference plane structure for fixing a potential reference for a plurality of wiring circuit trace layers that are electrically isolated there between by a plurality of printed circuit board layers and having a printed circuit board layer with a main surface, characterized by:

- a wire trace circuit layer applied to said main surface;

- a printed circuit board-insulation layer formed over said wire trace circuit layer;

- a reference plane applied over the printed circuit board insulation layer;

- a trench having an interior wall extending through and exposing the wire trace circuit layer, and the trench further extending through the insulation layer to the reference plane wherein the reference plane is exposed; and

- a conductive plating layer on the interior wall electrically connects the wire trace circuit layer to the reference plane.

10. (Currently pending) The printed circuit board of claim 9, wherein the trench completely encompasses the wire trace circuit layer.

11. (Currently pending) The printed circuit board of claim 9, wherein the reference plane is fixed at a ground potential.

12. (Currently pending) The printed circuit board of claim 9, wherein the reference plane is fixed at a reference voltage.

13. (Currently pending) A printed circuit board having a wiring connection structure, characterized by:

a first wire trace having a width and applied to a main surface of a printed circuit board layer and having a first terminal landing pad and having a first through hole having a non-circular cross section taken normal to a longitudinal axis of the first through hole and having an inner wall and with a major diameter and a minor diameter wherein the minor diameter is less than the width of the first wire trace and the major diameter is elongated and oriented along a longitudinal direction of the first terminal landing pad;

a first insulation layer formed over said first wire trace and having a

second through hole having an inner wall and having identical geometry and orientation as the first through hole and vertically aligned with the first through hole; and

a second wire trace applied to the first insulation layer and having a second terminal landing pad and having a third through hole having an inner wall and having identical geometry to the first through hole and aligned with the first through hole, and

wherein the inner wall of the first through hole, the inner wall of the second through hole, and the inner wall of the third through hole are plated with an electrically conductive material forming a plated hole which vertically intersects the first terminal pad and second terminal pad and electrically connects the first wire trace and the second wire trace.

14. (Currently pending) The printed circuit board of claim 13, wherein the major diameter is at least about twice that of the minor diameter.

15. (Currently pending) The printed circuit board of claim 13, wherein the major diameter is at least about three times that of the minor diameter.

16. (Currently pending) A printed circuit board having a wiring connection

structure, characterized by:

a first wire ~~circuit~~ trace having a first width and applied to a main surface of a printed circuit board layer and having a first terminal landing pad having a second width which is greater than the first width and having a first through hole having a non-circular cross section taken normal to a longitudinal axis of the first through hole and having an inner wall and with a major diameter and a minor diameter and wherein the minor diameter is less than the second width and wherein the major diameter is greater than the first width and is ~~directed~~ oriented along ~~and~~ a longitudinal direction within the first terminal landing pad;

an insulation layer formed over said first wire trace and having a second through hole having an inner wall and having identical geometry and orientation as the first through hole and vertically aligned with the first through hole; and

a second wire trace applied to the insulation layer and having a second terminal landing pad and having a third through hole having identical geometry to the first through hole and aligned with the first through hole, and wherein the inner wall of the first through hole, the inner wall of the second through hole, and the inner wall of the third through hole are plated with an electrically conductive

material forming a plated hole which vertically intersects the first terminal pad and second terminal pad and electrically connects the first wire trace and the second wire trace.

17-20. (Withdrawn from consideration)

21. (Currently pending) A printed circuit board having an EMI shielding structure for shielding a plurality of wire trace layers, characterized by:

a printed circuit board layer having a wire trace applied thereto;

an insulation layer; and

a grounding plane;

a first trench having an interior wall and forming a perimeter encompassing the wire trace and extending through the printed circuit board layer and extending to the ground plane and exposing said ground plane; and

an electrically conductive plating material applied upon the interior wall of the first trench and electrically connecting to the exposed ground plane providing ~~at least a partial~~ a perimeter shield for the trace.

22. (Cancelled)

23. (Currently pending) The printed circuit board of claim 21, further characterized by:

a second trench having an interior wall and spaced a distance from the first trench such that the wire trace extends between the first trench and second trench, the second trench ~~and~~ extending through the printed circuit board layer and extending to the ground plane exposing said ground plane,

wherein the interior wall of the second trench is plated with an electrically conductive plating material electrically connecting to the exposed ground plane thereby providing a double trench shield.

24. (Currently pending) The printed circuit board of claim 21, further characterized by:

an EMC sensitive track of conductive material extending wholly within a perimeter defined by the first trench and disposed between a plurality of circuit board insulation layers through which the first trench extends.

25. (Currently pending) A printed circuit board having an EMI shielding structure for shielding a plurality of wire trace layers, characterized by:

a plurality of printed circuit board layers having a plurality of wire trace layers, each printed circuit board layer separated by an insulation

layer and having a grounding plane layer;
a first trench extending from a top printed circuit board layer to the
grounding plane layer and the first trench having;
an electrically conductive plating applied over an interior wall of the first
trench and electrically connecting to the ground plane; and wherein
the first trench completely surrounds at least an area of the printed
circuit board layers.

26. (Currently pending) The printed circuit board of claim 25, further
characterized by:

a second trench disposed interior to the first trench and said second
trench extending substantially in parallel to the first trench;
and the second trench having an electrically conductive plating applied
over an interior wall thereof electrically connecting to the ground
plane and an EMC sensitive track extending in a printed circuit
board layer positioned between the first trench and the second
trench.

27. (Currently pending) The printed circuit board of claim 3 comprising at
least a second plated through hole, the second plated through hole having a
non-circular cross section which is different from the non-circular cross section

of the first plated through hole.

28. (Currently pending) The printed circuit board of claim 3 wherein the non-circular shaped cross section of the through hole is a cross, a "U", an "L", an "E", a square, a rectangle, a "double cross", a star, an oval, a continuous curve, or an irregular shape.

29. (Withdrawn from consideration)

30. (Currently pending) A printed circuit board having an EMI shielding structure for shielding a plurality of wire trace layers, characterized by:

- a plurality of printed circuit board layers having a plurality of wire trace layers, each printed circuit board layer separated by an insulation layer and having a grounding plane layer;

- a first trench extending from a top printed circuit board layer to the grounding plane layer and the first trench having an electrically conductive plating applied over an interior wall of the first trench and electrically connecting to the ground plane; and

- a second trench disposed interior to the first trench and said second trench extending substantially in parallel to the first trench and the second trench having an electrically conductive plating applied over

an interior wall thereof electrically connecting to the ground plane;

and

at least two EMC sensitive tracks extending in a printed circuit board layer positioned between the first trench and the second trench.